



1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16
VSS	VDD	VO	RS	R/W	E	DB0	DB1	DB2	DB3	DB4	DB5	DB6	DB7	LED+	LED-

VDD : 5.0V±5%  
 DISPLAY TYPE : TN, POSITIVE MODE  
 POLARIZER MODE : REFLECTIVE  
 CONNECTOR : ZEBRA  
 VIEW ANGLE : 6 O'CLOCK  
 DRIVING METHOD : 4.5V, 1/16 DUTY, 1/5BIAS  
 DISPLAY DRIVER : KS0066 OR EQUIVALENT  
 BACKLIGHT COLOR : NA  
 BACKLIGHT Vf : NA  
 BACKLIGHT If : NA  
 BEZEL FINISH : BLACK ELECTRO PLATING  
 OPERATING TEMP : 0°C TO +50°C  
 STORAGE TEMP : -10°C TO +60°C

DRAWN BY : F T T 2005-04-18  
 CHECKED BY :  
 Approve By :

**海南清华显示器科技开发有限公司**  
 HAINAN QINGHUA LCD TECHNOLOGY DEVELOPMENT CO.,LTD

UNITS: MM  
 TITL: CUSTOMER LCD  
 SHEET: 1 OF 1  
 SCALE: NTS

**UC162A-TP-RB-N**