



DOT DETAIL
SCALE 4:1

1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16
VSS VDD	VO	RS	R/W	E	DB0	DB1	DB2	DB3	DB4	DB5	DB6	DB7	LED+	LED-	

VDD : 5.0V±5%
 DISPLAY TYPE : HTN, POSITIVE MODE
 POLARIZER MODE : REFLECTIVE
 CONNECTOR : ZEBRA
 VIEW ANGLE : 6 O'CLOCK
 DRIVING METHOD : 4.5V, 1/16 DUTY, 1/5BIAS
 DISPLAY DRIVER : KS0066 OR EQUIVALENT
 BACKLIGHT COLOR : NA
 BACKLIGHT Vf : NA
 BACKLIGHT If : NA
 BEZEL FINISH : BLACK ELECTRO PLATING
 OPERATING TEMP : 0°C TO +50°C
 STORAGE TEMP : -10°C TO +60°C

DRAWN BY : F T T 2005-04-18
 CHECKED BY :
 Approve By :

海南清华显示器科技开发有限公司
 HAINAN QINGHUA LCD TECHNOLOGY DEVELOPMENT CO.,LTD

UNITS	MM
TITL	CUSTOMER LCD
SHEET: 1 OF 1	
SCALE: NTS	

REV: A1
 SIZE: A4
UC162F-HP-RB-N