


11.0(14.0) MAX.  
( ) FOR BACKLIGHT  
5.0(8.5) MAX.



SCALE 6:1

1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16
VSS	VDD	VO	RS	R/W	E	DB0	DB1	DB2	DB3	DB4	DB5	DB6	DB7	LED+	LED-

VDD : 5.0V±5%  
 DISPLAY TYPE : FSTN, POSITIVE MODE  
 POLARIZER MODE : TRANSFLECTIVE  
 CONNECTOR : ZEBRA  
 VIEW ANGLE : 6 O'CLOCK  
 DRIVING METHOD : 4.5V, 1/16 DUTY, 1/5BIAS  
 DISPLAY DRIVER : KS0066 OR EQUIVALENT  
 BACKLIGHT COLOR : WHITE  
 BACKLIGHT Vf : 3.4V (TYP)  
 BACKLIGHT If : 40mA (TYP)  
 BEZEL FINISH : BLACK ELECTRO PLATING  
 OPERATING TEMP : 0°C TO +50°C  
 STORAGE TEMP : -10°C TO +60°C

DRAWN BY : F T T 2005-04-18


CHECKED BY :

Approve By :



HAINAN QINGHUA LCD TECHNOLOGY DEVELOPMENT CO.,LTD

UC204A-FP-FB-N-LG-W



UNITS

MM

TITL CUSTOMER LCD

REV: A1 SHEET: 1 OF 1

SIZE: A4 SCALE: NTS