



DOT DETAIL
SCALE: 20:1

1	2	3	4	5	6	7	8	9	10
VSS	VDD	V0	RS	R/W	E	DB0	DB1	DB2	DB3
11	12	13	14	15	16	17	18	19	20
DB4	DB5	DB6	DB7	CS1	CS2	RST	VOUT	LED+	LED-

- VDD : 5.0V±5%
- DISPLAY TYPE : STN BLUE, NEGATIVE MODE
- POLARIZER MODE : TRANSMISSIVE
- CONNECTOR : ZEBRA
- VIEW ANGLE : 6 O'CLOCK
- DRIVING METHOD : 8.5V, 1/64 DUTY, 1/9BIAS
- DISPLAY DRIVER : KS0107 OR EQUIVALENT
- BACKLIGHT COLOR : WHITE
- BACKLIGHT Vf : 3.2V (TYP)
- BACKLIGHT If : 60mA (TYP)
- BEZEL FINISH : BLACK ELECTRO PLATING
- OPERATING TEMP : 0°C TO +50°C
- STORAGE TEMP : -10°C TO +60°C

DRAWN BY : F T T 2011-03-06
 CHECKED BY :
 Approve By :

海南清华显示器科技开发有限公司
 HAINAN QINGHUA LCD TECHNOLOGY DEVELOPMENT CO.,LTD

UG64128A1-BN-MB-N-LG-W

REV: A1
 SIZE: A4

SHEET: 1 OF 1
 SCALE: NTS

UNITS	MM
	CUSTOMER LCD